

# Latex Media (Matte Backlit Film)

## Technical Data Sheet

Product Name : ITP-LPMT3



### Description

A non-adhesive matte PET backlit film.

### Application

A matt 8 mil backlit translucent polyester film with a glossy finish that produces high resolution images when printed with Latex, Solvent or UV inks. An excellent solution for all frontlit or backlit applications.

### Properties

Base Materials		PET Film		
Item		Test Method	Description	Unit
Total Thickness		HETM-01-020	200 ± 5	µm
Total Weight		HETM-01-030	270 ± 5	g/m <sup>2</sup>
Tensile Strength	MD	ASTM D882A	11.5 ± 2	kgf/mm <sup>2</sup>
	TD		17 ± 2	kgf/mm <sup>2</sup>
Surface		-	Matte	-
Whiteness		HETM-03-070	90 ± 5	%
Opacity		HETM-03-080	70 ± 5	%
Gloss(60 Deg)		HETM-01-050	< 10	-
Adhesive Type		HETM-04-020	-	-
Adhesive Strength		HETM-04-040	-	gf/25mm
Ink absorption		HETM-02-040	Latex, Solvent, UV	-

To request a sample or for more information  
call 01993 862770 or email [info@inkteceu.com](mailto:info@inkteceu.com)

[www.inktec-europe.com](http://www.inktec-europe.com)

InkTec Europe Ltd : Bulford House : Supergas Industrial Estate : Downs Road : Witney : Oxfordshire : OX29 0SZ