

Latex Media (Clear Semi Glossy Film)

Technical Data Sheet

Product Name : ITP-LPST2RT



Introduction

A clear, transparent, semi gloss, PET film with a semi-permanent removable adhesive and film release liner.

Application

Designed to stick to any smooth surface. Apply to non-printable surfaces such as glass, aluminium or primed wood for striking visual effects. Providing excellent colour density and high definition images when printed with Latex, Solvent and UV inks.

Properties

Base Materials		PET Film		
Item		Test Method	Description	Unit
Total Thickness		HETM-01-020	180 ± 5	µm
Total Weight		HETM-01-030	230 ± 5	g/m ²
Tensile Strength	MD	ASTM D882A	11.5 ± 2	kgf/mm ²
	TD		17 ± 2	kgf/mm ²
Surface		-	Semi-glossy	-
Whiteness		HETM-03-070	90 ± 5	%
Opacity		HETM-03-080	70 ± 5	%
Gloss(60 Deg)		HETM-01-050	35 ± 5	-
Adhesive Type		HETM-04-020	Removable	-
Adhesive Strength		HETM-04-040	< 50	gf/25mm
Ink absorption		HETM-02-040	Latex, Solvent, UV	-

To request a sample or for more information

call 01993 862770 or email info@inkteceu.com

www.inktec-europe.com

InkTec Europe Ltd : Bulford House : Supergas Industrial Estate : Downs Road : Witney : Oxfordshire : OX29 0SZ