


# **Product description**

- An aqueous premium matte polypropylene banner display film for banner applications
- Fast drying universal compatibility with Aqueous Pigmented, Latex and UV inks
- Produces high quality vibrant images
- Very durable and tear resistant

### **Specifications**

Length	30m	Inner Core	2" (3" core optional)
Weight	145gsm	Surface	Matte
Caliper	190µm	Base Material	Polypropylene

#### Uses



Indoor & outdoor signage, roll up banners for exhibition stands and retail promotions

# **Printing and handling**

- Recommended conditions for use: 10~30°C / 30~65% RH
- To optimize the printing quality, printer needs to be set for highest print quality
- Laminating is optional and can protect the image from physical damage and to decrease image-fading
- Allow image to dry completely prior to handling and laminating
- One year storage in original package under recommended temperature 10°~25°C, 30~ 50% RH

# **Application tips**

- When printing with Latex 300 Series printers it is recommended to set the appropriate pass and heating temperatures, this will ensure that there are no material deformation or drying issues
- It is recommended to test prior to use, samples are available, please contact us for details



\*Important information: It is the responsibility of the purchaser to test and determine the suitability of the material. Printer and ink change may affect results. information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.